



DOUBLE ACTION SANDERS -1-

APPLICATIONS

Widely used at various industries of car body repairing, wooden working, metal working, FRP working, etc. with U-TOOL's excellent sanding program. Tools are of low vibration, low gravity center, well-balanced.

U-51

1.2" Mini Double Action Sande



U-52

Mini Double Action Sander



U-54

4" Double Action Sander



U-55

5" Double Action Sander





U-551

5" Double Action Sander



U-56

6" Double Action Sander



Velcro Hard Pad 123mm

Velcro Soft Pad 123mm

U-556

5" Double Action Sander



U-551S

5" Double Action Sander



with one-body pad

Model	Pad Size (mm)	Speed (no load) rpm	Orbit Dia. (mm)	Air Cons. (L/min)	Pad Screw Size (mm)	Air Inlet (inch PT)	Net Weight (kg)	Length (mm)	Noise Level (dBA)
U-51	30	8,500	3	140	-	1/4PT	0.48	175	75
U-52	45/72	10,000	3	280	5/16-24UNF	1/4PT	0.71	198	83
U-54	98	9,000	5	340	5/16-24UNF	1/4PT	0.7	165	78
U-551/551S	123	9,000	5	340	5/16-24UNF	1/4PT	0.69	175	78
U-55	123	10,000	5	380	5/16-24UNF	1/4PT	0.9	175	78
U-56	148	10,000	5	380	5/16-24UNF	1/4PT	0.9	185	78
U-556	123	11,000	6	400	5/16-24UNF	1/4PT	1.7	265	80