

APPLICATIONS

Widely used at various industries of car body repairing, wooden working, metal working, FRP working.

■ U-55X 5"/6" Double Action Sander [Light-weight]



Model	Pad Size (mm)	Speed (mm)	Orb. Dia. (mm)	Air Cons. (L/min)	Pad Screw Size (mm)	Air Inlet (PT)	Weight (kg)	Length (mm)	Noise (dBA)
U-55X	123/148	12000	5	380	5/16-24UNF	1/4	0.75/0.77	155/165	75

■ U-55J 5"/6" Double Action Sander [10mm orbit dia. High power]



Model	Pad Size (mm)	Speed (mm)	Orb. Dia. (mm)	Air Cons. (L/min)	Pad Screw Size (mm)	Air Inlet (PT)	Weight (kg)	Length (mm)	Noise (dBA)
U-55J	123	9000	10	350	5/16-24UNF	1/4	1.0	155/165	83

■ U-521 Mini Double Action Sander ■ U-55W Wet Double Action Sander



Model	Pad Size (mm)	Speed (rpm)	Orbit Dia. (mm)	Air Cons. (L/min)	Pad Thread Dia. (mm)	Air Inlet (inch PT)	Net Weight (kg)	Length (mm)	Noise (dBA)
U-521	48	12,500	3	680	6	1/4	0.85	180	85
U-55W	123	8,500	5	380	5/16-24UNF	1/4	0.93	225	78